

.....

HTFU XRV-P

8-way compact cassette 60x60



Ultra-compact design
22 dB(A) (2.20-2.80 kW)
high silence

Condensate drainage pump with
the possibility of raising the drain
up to 500 mm from the lower level

360° air diffusion
**The controller must be purchased
as an accessory**

Model		HTFU 225 XRV-P		HTFU 285 XRV-P		HTFU 365 XRV-P		HTFU 455 XRV-P	
Rated capacity	Cooling	kW	2.20	2.80	3.60	4.50			
	Heating	kW	2.40	3.20	4.00	5.00			
Electrical data									
Power supply		Ph-V-Hz	1-220~240V-50Hz						
Absorbed power		W	35	35	40	50			
Product specifications									
Dimensions		LxHxD	630x260x570						
Net weight		Kg	18			19.2			
Sound power level ¹	Max~Min	dB(A)	51~38			56~43			
	Max~Min	dB(A)	35~22			41~28			
Treated air volume ¹	Max~Min	m ³ /h	576~405			604~400			
Diameter of the connections	Liquid/Gas	mm (inch)	6.35 (1/4") / 12.7 (1/2")						
	Condensate	mm	32						
Accessories									
Decorative panel			TFP 155 XRV-P						
Panel dimensions		LxHxD	647x50x647						
Net weight		Kg	2.5						
Remote control			DHIR-5-6-XRV-K-P						
Wired control			DHW-5-6-XRV-P						
Optional parts									
Centralized control			DHC-8-64-XRV-P						

1. Values relating to the Max and Min speeds of 7 levels that can be set by remote control.

HTBU XRV-P

8-way cassette 84x84



Optimized fan design to
attenuate air resistance and
reduce sound level

**Predisposition for the
connection of a duct
for the introduction of
external air**

Condensate drainage
pump with the possibility of
raising the drain up to 750
mm from the lower level

**The controller must
be purchased as an
accessory**

Model		HTBU 565 XRV-P		HTBU 715 XRV-P		HTBU 905 XRV-P		HTBU 1125 XRV-P		HTBU 1405 XRV-P	
Rated capacity	Cooling	kW	5.60	7.10	9.00	11.20	14.00				
	Heating	kW	6.30	8.00	10.00	12.50	16.00				
Electrical data											
Power supply		Ph-V-Hz	1-220~240V-50Hz								
Absorbed power		W	31	46	75	94					
Product specifications											
Dimensions		LxHxD	840x230x840				840x300x840				
Net weight		Kg	23.2				28.4		30.7		
Sound power level ¹	Max~Min	dB(A)	56~47		58~47		61~50		64~52		
	Max~Min	dB(A)	43~34		45~34		47~36		50~38		
Treated air volume ¹	Max~Min	m ³ /h	1029~704		1200~748		1596~1034		1727~1224		
Diameter of connections	Liquid/Gas	mm (inch)	9.52 (3/8") / 15.9 (5/8")								
	Condensate	mm	32								
Accessories											
Decorative panel			TBP 712 IHXR								
Panel dimensions		LxHxD	950x70x950								
Net weight		Kg	5.8								
Remote control			DHIR-5-6-XRV-K-P								
Wired control			DHW-5-6-XRV-P								
Optional parts											
Centralized control			DHC-8-64-XRV-P								

1. Values relating to the Max and Min speeds of 7 levels that can be set by remote control.