

.....

HUCU XRV-P

Ducted medium static pressure



Only 210 mm high
(2.20-7.10 kW) compact design
perfect for use in hotels

Available static pressure:
50 Pa (2.20-7.10 kW);
100 Pa (9.00-11.20 kW)

Air intake from bottom or rear
Condensate drain pump included with
possibility of raising the discharge up
750 mm from the lower height

Compatible with systems **AIRZONE**
**The control must be
purchased as an accessory**

Model			HUCU 225 XRV-P	HUCU 285 XRV-P	HUCU 365 XRV-P	HUCU 455 XRV-P
Rated capacity	Cooling	kW	2.20	2.80	3.60	4.50
	Heating	kW	2.60	3.20	4.00	5.00
Electrical data						
Power supply		Ph-V-Hz	1-220~240V-50Hz			
Absorbed power		W	40	40	45	92
Product specifications						
Dimensions	LxHxD	mm	780x210x500			1000x210x500
Net weight		Kg	18			21.5
Sound power level ¹	Max~Min	dB(A)	50~41		51~43	54~43
	Max~Min	dB(A)	32~23		33~25	36~25
Sound pressure level at 1.4 m ¹	Max~Min	dB(A)	32~23		33~25	36~25
	Max~Min	m ³ /h	520~300		580~370	800~400
Fan static pressure	Std/Max	Pa	10/50			
Diameter of connections	Liquid/Gas	mm (inch)	6.35 (1/4") / 12.7 (1/2")			
	Condensate	mm	25			
Accessories						
Remote control			DHIR-5-6-XRV-K-P			
Wired control			DHW-5-6-XRV-P			
Optional parts						
Centralized control			DHC-8-64-XRV-P			

1. Values relating to the Max and Min speeds of 7 levels that can be set by remote control.

Model			HUCU 565 XRV-P	HUCU 715 XRV-P	HUCU 905 XRV-P	HUCU 1125 XRV-P
Rated capacity	Cooling	kW	5.60	7.10	9.00	11.20
	Heating	kW	6.30	8.00	10.00	12.50
Electrical data						
Power supply		Ph-V-Hz	1-220~240V-50Hz			
Absorbed power		W	92	98	120	200
Product specifications						
Dimensions	LxHxD	mm	1000x210x500	1220x210x500	1230x270x775	
Net weight		Kg	21.5	27.5	37	
Sound power level ¹	Max~Min	dB(A)	54~46	55~46	55~46	57~51
	Max~Min	dB(A)	36~28	37~28	37~28	39~33
Sound pressure level at 1.4 m ¹	Max~Min	dB(A)	36~28	37~28	37~28	39~33
	Max~Min	m ³ /h	830~560	1000~680	1260~780	1500~1080
Fan static pressure	Std/Max	Pa	10/50		20/100	
Diameter of connections	Liquid/Gas	mm (inch)	9.52 (3/8") / 15.9 (5/8")			
	Condensate	mm	25			
Accessories						
Remote control			DHIR-5-6-XRV-K-P			
Wired control			DHW-5-6-XRV-P			
Optional parts						
Centralized control			DHC-8-64-XRV-P			

1. Values relating to the Max and Min speeds of 7 levels that can be set by remote control.